


# fura dining table structure

design Form Us With Love



## ESTRUCTURA



PE - Polietileno  
color básico

6420



## PESO BRUTO:

kg 5,6

## COMPLEMENTOS:

**A4461**

Sistema de fijación en el  
suelo

**A4601**


Kit de arena seca

# fura dining table structure light

design Form Us With Love



## ESTRUCTURA



PE - Polietileno  
color básico

8420



98

## KIT LUZ

## PESO BRUTO:

kg 5,6

A4744 kit LED RGB de batería para interior/exterio bluetooth

## DETALLES:





























Necesaria 1 Kit de iluminación

## COMPLEMENTOS:


A4197  
Base de estabilización

A4194  
Base de estabilización  
y fijación

# fura dining table structure parte superior

PARTE SUPERIOR	HPL color básico	DIMENSIONES:	PESO BRUTO:
 70	A4490 	 	Cm 69x1 h Kg 6,2
	A4491 	 	Cm 69x1 h Kg 6
 80	A4494 	 	Cm 79x1 h Kg 8
	A4495 	 	Cm 79x1 h Kg 7,7
 70	A4488 	 	Cm 69x69x1 h Kg 7,8
	A4489 	 	Cm 69x69x1 h Kg 7,4
 80	A4492 	 	Cm 79x79x1 h Kg 10
	A4493 	 	Cm 79x79x1 h Kg 9,6

## TESTS (ART. 6420)

Declaration of conformity issued by  with the 80x80 cm top

Conforms to the requirements of resistance, durability and safety, 2<sup>nd</sup> level EN 15372:2016

Tests carried out as per:  
 EN 15372:2016, clause 6  
 EN 15372:2016, clause 5.1 - 5.2  
 EN 1730:2012, clause 6.2  
 EN 1730:2012, clause 6.3  
 EN 1730:2012, clause 6.4.2  
 EN 1730:2012, clause 6.5  
 EN 1730:2012, clause 6.6  
 EN 1730:2012, clause 6.9  
 EN 1730:2012, clause 7.2 - kg 38

**Attention** to ensure stability under a vertical pressure, the part must be stabilized according to point 7.2 of EN 1730:2012.

To do this, inert material (es. dried sand) must be poured into the hole at the bottom of the base. The amount of the material will vary according to the article:

art. A4490/A4491 70 cm - kg 15  
 art. A4494/A4495 80 cm - kg 18  
 art. A4488/A4489 70x70 cm - kg 30

Finally, close the hole by screwing the threaded cap back on.