

# fura table

design Form Us With Love



## STRUTTURA/STRUCTURE

PE - Polietilene/Polyethylene  
colore base/basic colour

6295



## GROSS WEIGHT:

kg 6,7

## ACCESSORIES:

**A4461**  
Sistema di fissaggio a  
terra/Fixing kit system


**A4601**  
Kit sabbia essiccata/  
Dried sand kit

# fura table light

design Form Us With Love



## STRUTTURA/STRUCTURE



## GROSS WEIGHT:

kg 6,7

**PE** - Polietilene/Polyethylene  
**colore base/basic colour**

8295



98

## KIT LUCE/LIGHT KIT

**A4364** - Kit led RGB a batteria con spina/  
RGB led light kit with battery and plug



## dettagli/details

Kit LED RGB a batteria powered by Smart&Green/  
RGB LED Kit with battery powered by Smart&Green  
Autonomia 6 ore circa, alla massima intensità/  
Autonomy 6 hours on average at maximum power

Luce: bianca, colorata, a rotazione/  
Light: white, coloured, rotating colours

Telecomando/Remote control

Base di ricarica con spina europea bipolare/  
Charger with european bipolar plug

## LUCE/LIGHT




# fura table top

## GROSS WEIGHT:

A4463 kg 4,9  
 A4464 kg 4,6  
 A4468 kg 6  
 A4469 kg 5,7  
 A4625 kg 13,2  
 A4626 kg 12,4  
 A4470 kg 20  
 A4471 kg 18,7  
 A4604-A4605 kg 5,2

## PIANO/TOP



60

## DETAILS:

**Necessita di due strutture per il piano/  
 Needs two structures for the top**

A4625  
 A4626  
 A4470  
 A4471



60




120



180


## HPL

colore base/basic colour



## WERZALIT

colore base/basic colour



## TESTS

Declaration of conformity issued by **CATAS**  
 with the 180x60 cm top

Conforms to the requirements of resistance,  
 durability and safety, 2<sup>nd</sup> level EN 15372:2016

Tests carried out as per:

EN 15372:2016, clause 6  
 EN 15372:2016, clause 5.1 - 5.2  
 EN 1730:2012, clause 6.2  
 EN 1730:2012, clause 6.3  
 EN 1730:2012, clause 6.4.2  
 EN 1730:2012, clause 6.5  
 EN 1730:2012, clause 6.6  
 EN 1730:2012, clause 7.2

The declaration of conformity and related tests refer  
 only to full-body coloured articles.

**Attention** to ensure stability under a vertical  
 pressure, the part must be stabilized according  
 to point 7.2 of EN 1730:2012.

To do this, inert material (es. dried sand)  
 must be poured into the hole at the bottom of  
 the base. The amount of the material will vary  
 according to the article:

art. A4468/A4469 60x60 cm - kg 16  
 art. A4625/A4626 120x60 cm - kg 26  
 art. A4470/A46471 180x60 cm - kg 20

Finally, close the hole by screwing the threaded  
 cap back on.