


# gumball armchair

design Alberto Brogliato



## STRUTTURA/STRUCTURE



## GROSS WEIGHT:

6246 kg 17,5

6546 kg 18,8

6243 kg 22,5

## ACCESSORIES:

### A4670

Sistema di fissaggio a terra/Fixing kit system

### A4601

Kit sabbia essiccata/  
Dried sand kit

**PE** - Polietilene/Polyethylene  
**colore base/basic colour**

6246



C2



G9



M9



N2



N4



87

**PE** - morbido con palline/soft with little balls  
**finitura speciale/special finishing**

6243



98

**PE** - Polietilene/Polyethylene  
**laccati/lacquered**

6546



03



44

## TESTS

Declarations of conformity issued by **CATAS**

Conforms to the requirements of resistance, durability and safety, 1<sup>st</sup> level EN 16139:2013

Tests carried out as per:

EN 16139:2013 + AC:2013

EN 1728:2012 + AC:2013

EN 1022:2005

Conforms to the mechanical and structural safety requirements of ANSI BIFMA X5.1-2017

Tests carried out as per:

ANSI-BIFMA X5.1-2017/10

ANSI-BIFMA X5.1-2017/7

ANSI-BIFMA X5.1-2017/15

ANSI-BIFMA X5.1-2017/6

ANSI-BIFMA X5.1-2017/11


# gumball armchair light

design Alberto Brogliato



## STRUTTURA/STRUCTURE

**PE** - Polietilene/Polyethylene  
**colore base/basic colour**



**8246**



## GROSS WEIGHT:

kg 17,5

## ACCESSORIES:

**A4670**

Sistema di fissaggio a terra/Fixing kit system

## TESTS

Declarations of conformity issued by **CATAS**

Conforms to the requirements of resistance, durability and safety, 1<sup>st</sup> level EN 16139:2013

Tests carried out as per:

EN 16139:2013 + AC:2013

EN 1728:2012 + AC:2013

EN 1022:2005

Conforms to the mechanical and structural safety requirements of ANSI BIFMA X5.1-2017

Tests carried out as per:

ANSI-BIFMA X5.1-2017/10

ANSI-BIFMA X5.1-2017/7

ANSI-BIFMA X5.1-2017/15

ANSI-BIFMA X5.1-2017/6

ANSI-BIFMA X5.1-2017/11

## KIT LUCE/LIGHT KIT

**A4182** - outdoor



## dettagli/details

Guscio in policarbonato/  
Polycarbonate shell

Guarnizione a tenuta/  
Gasket seal

Cavo nero/  
Black cable

Spina Schuko antispruzzo/  
Anti-splash Schuko plug

Lunghezza cavo 280 cm/  
Wire length 280 cm

Predisposizione per  
base di stabilizzazione/  
Arrangement for stability base

**LUCE/LIGHT** 1 x 20 W

