


# ohla sofa

design Alberto Brogliato



## STRUTTURA/STRUCTURE



## GROSS WEIGHT:

6304 kg 34,2

6575 kg 37,4

## ACCESSORIES:

### A4668

Sistema di fissaggio  
a terra (2 kit)/  
Ground fixing kit (2 kit)

### A4601

Kit sabbia essiccata/  
Dried sand kit

PE - Polietilene/Polyethylene  
colore base/basic colour

### 6304




C2 L4 M9 N2



N4 69 87

PE - Polietilene/Polyethylene  
laccati/lacquered

### 6575



D7 03 07

## TESTS

Declarations of conformity issued by **CATAS**

Conforms to the requirements of resistance, durability  
and safety, 1<sup>st</sup> level EN 16139:2013

Tests carried out as per:

EN 16139:2013 + AC:2013

EN 1728:2012 + AC:2013

EN 1022:2005

Conforms to the mechanical and structural safety  
requirements of ANSI BIFMA X5.4-2012

Tests carried out as per:

ANSI-BIFMA X5.4-2012/7

ANSI-BIFMA X5.4-2012/5

ANSI-BIFMA X5.4-2012/8

ANSI-BIFMA X5.4-2012/6

ANSI-BIFMA X5.4-2012/14

ANSI-BIFMA X5.4-2012/12

ANSI-BIFMA X5.4-2012/15

ANSI-BIFMA X5.4-2012/9

ANSI-BIFMA X5.4-2012/10

ANSI-BIFMA X5.4-2012/11

ANSI-BIFMA X5.4-2012/16

ANSI-BIFMA X5.4-2012/17

ANSI-BIFMA X5.4-2012/21


# ohla sofa light

design Alberto Brogliato



## STRUTTURA/STRUCTURE

PE - Polietilene/Polyethylene  
colore base/basic colour



8304

98

## GROSS WEIGHT:

kg 34,2

## ACCESSORIES:

### A4668

Sistema di fissaggio  
a terra (2 kit)/  
Ground fixing kit (2 kit)

Necessita di 2 Kit Luce/  
Needs 2 Light Kit

## TESTS

Declarations of conformity issued by **CATAS**

Conforms to the requirements of resistance, durability  
and safety, 1<sup>st</sup> level EN 16139:2013

Tests carried out as per:

EN 16139:2013 + AC:2013

EN 1728:2012 + AC:2013

EN 1022:2005

Conforms to the mechanical and structural safety  
requirements of ANSI BIFMA X5.4-2012

Tests carried out as per:

ANSI-BIFMA X5.4-2012/7

ANSI-BIFMA X5.4-2012/5

ANSI-BIFMA X5.4-2012/8

ANSI-BIFMA X5.4-2012/6

ANSI-BIFMA X5.4-2012/14

ANSI-BIFMA X5.4-2012/12

ANSI-BIFMA X5.4-2012/15

ANSI-BIFMA X5.4-2012/9

ANSI-BIFMA X5.4-2012/10

ANSI-BIFMA X5.4-2012/11

ANSI-BIFMA X5.4-2012/16

ANSI-BIFMA X5.4-2012/17

ANSI-BIFMA X5.4-2012/21

## KIT LUCE/LIGHT KIT

### A4183 - indoor



#### dettagli/details

Cavo trasparente/  
Transparent cable

Pulsantiera a pedale/  
Foot switch

Spina europea bipolare/  
European bipolar plug

Lunghezza cavo 370 cm/  
Wire length 370 cm

Predisposizione per  
base di stabilizzazione/  
Arrangement for stability base

### LUCE/LIGHT 1 x 20 W



### A4182 - outdoor



#### dettagli/details

Guscio in policarbonato/  
Polycarbonate shell

Guarnizione a tenuta/  
Gasket seal

Cavo nero/  
Black cable

Spina Schuko antispruzzo/  
Anti-splash Schuko plug

Lunghezza cavo 280 cm/  
Wire length 280 cm

Predisposizione per  
base di stabilizzazione/  
Arrangement for stability base

### LUCE/LIGHT 1 x 20 W

